

WESTEC EQUIPMENT INTERNATIONAL LTD.

1514 Bay St. North Vancouver, B.C., Canada, V7J 1B3

Phone: (604) 988-1130

Fax: (604) 988-1173

BOW THRUSTER SPECIFICATIONS

HYDRAULIC DRIVE UNITS

	SIZES		
	18"	22"	26"
HYDRAULIC PRESSURE (PSI)	2000	2000	2000
OIL SUPPLY (U.S.G.P.M. MAX)	50	60	75
THRUST (LBS.)	850	1200	1900
NOMINAL HORSEPOWER AT THRUSTER	60	70	90
OVERALL TUNNEL LENGTH (INCHES)	17	20	20 1/2
TUNNEL O.D. (INCHES)	18 1/2	22 5/8	26 1/2
MATERIAL OPTIONS AVAILABLE	MILD STEEL	MILD STEEL	MILD STEEL
	ALUMINUM	ALUMINUM	ALUMINUM
	316 S.S.	316 S.S.	316 S.S.

NOTE 1) ALL ALUMINUM AND STAINLESS THRUSTERS HAVE STAINLESS STEEL PROPELLERS

NOTE 2) MILD STEEL THRUSTERS HAVE BRONZE PROPELLERS

NOTE 3) ALL THRUSTER HOUSINGS ARE FABRICATED NOT CAST

DELIVERY: NORMALLY 6 WEEKS